

Multilock Steel Stoppers with Centralising Arms for closing pipes during welding



General Description

For closing off Oil and Gas Pipelines whilst welding or other repair work is carried out. Plugs are supplied with Double Seals to make the Stoppers more stable in the Pipe. The Centralising Arms assist in locating the Stopper in the centre of the Pipe.

Features and Benefits


Pressure Plates are made of steel plate. Rubber Seals are commercial grade rubber mouldings.

Options

Pressure Gauge can be fitted for ease of checking the pressure in the pipeline.

A 2nd 1" Outlet can be fitted to the top of the Stopper, fitted with a Hose Coupling. A 3m Hose is fitted to this Coupling to allow gases to be vented out of the Pipe during welding work to avoid the risk of explosion.

Chemical resistant Rubber Seals can be supplied.



Multilock Steel Stoppers with Centralising Arms for closing pipes during welding

Specification and Dimensions

Dia Inch	Pipe Min	ID Max	Insert Into Pipe	Water Way	Maximum Pressure	Weight of Plug	Length of Plug
10"	239	275	250mm	2"	5p.s.i.	13.5 kg	600mm
12"	298	320	250mm	2"	5p.s.i.	13.5 kg	600mm
14"	348	400	250mm	2"	5p.s.i.	13.5 kg	600mm
16"	384	450	250mm	2"	5p.s.i.	13.5 kg	600mm
18"	435	482	250mm	2"	5p.s.i.	13.5 kg	600mm
20"	480	530	250mm	2"	5p.s.i.	15.0 kg	600mm
22"	535	578	250mm	2"	3p.s.i.	20.0 kg	600mm
24"	590	640	250mm	2"	3p.s.i.	24.0 kg	600mm
26"	635	690	250mm	2"	3p.s.i.	27.0 kg	600mm
28"	690	740	250mm	2"	3p.s.i.	31.0 kg	600mm
30"	740	786	250mm	2"	3p.s.i.	39.0 kg	600mm
32"	785	835	250mm	2"	3p.s.i.	45.0 kg	600mm
34"	825	880	250mm	2"	3p.s.i.	48.0 kg	600mm
40"	990	1040	250mm	2"	3p.s.i.	63.0 kg	600mm
46"	1140	1190	250mm	2"	3p.s.i.	93.0 kg	600mm